

# Eternity™1

**PREMIUM RUBBER UNDERLAYMENT**  
Advanced Underlayment for LVT/LVP, WPC/SPC,  
Laminate, Engineered Wood and Hardwood

## APPLICATION

- RESIDENTIAL
- COMMERCIAL

## APPROVED FOR USE UNDER

- LUXURY VINYL TILES AND PLANKS
- LAMINATE
- ENGINEERED WOOD
- HARDWOOD
- DIRECT ATTACHED LAMINATE AND VINYL FLOORING PRODUCTS

## DIMENSIONS AND PACKAGING

- ROLL SIZE **200 / SF**
- ROLL WIDTH **36"**
- ROLL WEIGHT **22 LBS**
- ROLLS/PALLET **24**
- PALLETS/TRUCK **52 DOUBLE STACKED**
- MATERIAL COMPOSITION **RUBBER**
- THICKNESS **1.8 MM**
- DENSITY **25LB/FT<sup>3</sup>**

## SPECIFICATIONS +/- 15%

- COMPRESSION SET **- ASTM D 1055-97**  
(22H, 70C)- 16%
- INDENTATION **- ASTM F1914 - 12%**
- SMOKE DENSITY **- ASTM A662**  
LESS THAN 89 MAX
- FLAMMABILITY TEST **- ASTM D 2859**  
(DOC FF 1-70) - PASS
- THERMAL RESISTANCE **0.205**  
(R-VALUE)
- ANTIMICROBIAL **YES**  
PROTECTION
- INDOOR AIR QUALITY **CRI CERTIFIED FOR LOW**  
**EMITTING MATERIALS**
- INSTALLATION **FLOAT, DOUBLE GLUE, SINGLE**  
METHODS\* **GLUE, NAIL DOWN, STAPLE**
- WARRANTY **LIMITED LIFETIME**

## APPROVED SUBSTRATES

- COMPLETELY CURED CONCRETE
- INTERIOR PLYWOOD
- CEMENT BACKER UNITS
- PROPERLY PREPARED OSB
- GYPCRETE

## SOUND RATINGS OVER 6" SLAB

LUXURY VINYL TILES & PLANKS

**Up to: DELTA 27DB, IIC 73, STC 63**

LAMINATE AND WOOD PRODUCTS

**Up to: DELTA 23DB, IIC 67, STC 63**

## SUSTAINABILITY AND LEED®

- CONTENT **100% VIRGIN LATEX**  
**RUBBER WITH RECYCLED**  
**TIRE CRUMB**
- RECYCLABILITY **100% POST CONSUMER**
- CERTIFICATION **GREEN LABEL PLUS**
- LEED® CREDIT EQ 4.3 **LOW-EMITTING**  
**MATERIALS**
- LEED® CREDIT MRc5.1, 5.2 **REGIONAL CONTENT**  
**20-30%**
- LEED® CREDIT IEQp3 **MINIMUM ACOUSTICAL**  
**PERFORMANCE**
- LEED® MRC4 **RECYCLED CONTENT**  
**10-20%**



Made in Canada with  
North American  
Raw Materials



**GLP103**

\*See installation instructions for guidelines and limitations on these methods.

